



The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Tuesday, October 31, 2017** at 12:15 a.m. Eastern Time. Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=C0028695&Standard=061&>

NSF/ANSI 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#). Click here for the definitions of [Water Contact Temperatures denoted in these Listings](#).

Pall Filter Specialists, Inc.

100 Anchor Road

P.O. Box 735

Michigan City, IN 46361

United States

800-348-3205

219-879-3307

[Visit this company's website \(http://www.fsfilters.com\)](http://www.fsfilters.com)

Facility : Grand Island, NE

Mechanical Devices

Trade Designation

Filtration Devices/Components

CBCP-0012-[Y]-0150-N-[II]-[T]-[OO]-[T][1]

**Water Water
Contact Contact
Size Temp Material**

[2] CLD 23 MLTPL

CBFP-0012-[Y]-0150-N-[II]-[T]-[OO]-[T][1]

[2] CLD 23 MLTPL

Cartridge Filter Vessels FSMC [AA][BB][Z][CCC][N][SS][Z][KK][P][II][U][Y]N[3]

[4] CLD 23 MLTPL

FSPN[XXXX]-[Y]-[WWWW]-N[1]

[2] CLD 23 MLTPL

[1] [XXXX] Model number

0085, 0250, 0355, 0800, 1100, 2000, 2500, 3000, 3500, 4000, 4200, 4500,
4800, 5000

[Y] Vessel Material

B, C, D or E

[WWWW] Vessel Pressure Rating

0100, 0150, 0300

[II] Inlet Size

Use basic pipe size

[00] Outlet Size

Use basic pipe size

[T] Inlet or Outlet Type

C, D, F, H, I, K, M, N, P, S, T, W

[2] Certified for a minimum daily flow of 50,000 L.

[3] FSMC cartridge filter vessel suffixes:

AA indicates number of cartridges (03, 06, 12, 18, 27, 36, 42, 50, 59, 70, 81)

BB indicates cartridge length (20, 30 or 40)

Z indicates vessel material (B,C,D or E)

CCC indicates vessel pressure rating (0150 or 0300)

N indicates internal finish (none)

SS indicates inlet size (1D, 02, 03, 04, 06, 08, 10)

Q indicates inlet type (D, F, H, I, K, M, or F)

KK indicates outlet size (1D, 02, 03, 04, 06, 08, 10)

P indicates outlet type (D, F, H, I, K, M, or F)

II indicates nozzle configuration (06 or 08)

U indicates cartridge type (J)

Y indicates Lid Opening (1, 2 or 3)

N indicates jacket type (none)

[4] Certified for a minimum daily flow of 17,280 gallons.

Facility : Soddy Daisy, TN**Mechanical Devices****Trade Designation**

	Water	Water
	Contact	Contact
Trade Designation	Size	Temp
		Material

Filtration Devices/Components

POLYMICRO® Microfiber Filter Bag (BMMF[W]P2P61)[1]	[2]	CLD 23	MLTPL
POLYMICRO® Microfiber Filter Bag (BPOMF[X]PP2P61)[1]	[2]	CLD 23	MLTPL
POLYMICRO® Seamless Filter Bag (BOS[Y]PP2P61)[1]	[2]	CLD 23	MLTPL
POLYMICRO® Seamless Gradient Filter Bag (BOSG[Z]PP2G61)[1]	[2]	CLD 23	MLTPL
Vorex Cartridge CMMC [XXX][YY][DD]Z61[5]	[4]	CLD 23	MLTPL
Vorex Cartridge CMMF[XXX][YY][DD]Z61[5]	[4]	CLD 23	MLTPL
VorexHP Cartridge CMHP[XXX][YY][DD]Z61[3]	[4]	CLD 23	MLTPL

[1] [W] - BMMF Micron Rating (Nominal)

1
3
5
10
25
50
75
100

[X] - BPOMF Micron Rating (Nominal)

1A - 1
2A - 2
10A - 10
25A - 25

[Y] - BOS Micron Rating (Absolute)

1
3
5
10
25
35
50
75
100

[Z] - BOSG Micron Rating (Absolute)

3
5
10
25
50
75
100

[2] Size 2 bags are 7" x 32". Certified for a minimum daily flow of 50,000 liters.

[3] VorexHP CMHP Cartridge suffixes:

XXX indicates micron rating (0005, 001, 003, 005, 010, 025, 035, 050, 075, or 100)

YY indicates length of cartridge (9.75, 10, 19.5, 20, 29.25, 29.75, 30, 40)

DD indicates end fitting options (A, B or C)

VorexHP CMHP Cartridge suffixes:

XXX indicates micron reading (001, 003, 005, 010, 025, 035, 050, 075, or 100)

YY indicates length of cartridge (9.75, 10, 19.5, 20, 29.25, 29.75, 30, 40)

DD indicates end fitting options (A, B or C)

[4] Certified for a minimum daily flow of 2,800 gallons per 10" equivalent cartridge.
Certified for cartridge outer diameters 2.5" - 5.5".

[5] Vorex CMMF and CMMC Cartridge suffixes:

XXX indicates micron reading (001, 005, 010, 025, 050, 075, 100 or 150)

YY indicates length of cartridge (9.75, 10, 19.5, 19.75, 20, 29.25, 29.5, 29.75, 30, 39, 39.5, 39.75, 40)

DD indicates end fitting options (A, B or C)

Number of matching Manufacturers is 1

Number of matching Products is 11

Processing time was 0 seconds