



Pall IMPRO™: Intelligent Maximum Performance Reverse Osmosis

impro™

IMPRO™ Reverse Osmosis (RO) systems are designed to maximize water recovery, consume less energy and minimize membrane fouling and scaling. These reliable units reduce waste streams by 50 — 80% while easily handling challenging feedwaters.

Featuring patented closed circuit reverse osmosis (CCRO) technology, Impro systems are ideal for extracting purified water from a wide range of applications using standard RO membrane elements and components. The smart configuration gives operators direct control of recovery rate, permeate flow and offers unmatched flexibility and ease of use.

THE BENEFITS

- **Higher Recovery:** Packaged filtration system recovers up to 95% of wastewater, significantly more than conventional RO
- **Minimum Waste Disposal:** Highest guaranteed recovery reduces disposal costs compared to traditional membrane technologies
- **Intelligent Operation:** Automatically adapts to variations in feed water composition, temperature, and flow
- **Reduced Energy Consumption:** Operates near thermodynamic minimum



TYPICAL APPLICATIONS

- Industrial boiler feed or cooling tower makeup
- Brine minimization
- Brackish water treatment
- Municipal wastewater reuse

STANDARD FEATURES

Automatic response to feed variations

Programmable logic controller with remote monitoring and control functionality

Chemical dosing systems

NSF-certified components

OPTIONAL FEATURES

Membrane pretreatment

Clean-in-Place (CIP) and flushing systems

Mixed-bed permeate polishing

Transfer pumps, storage tanks

OPERATING PARAMETERS

Adjustable Recovery 75 — 98%

Rejection 95.0 — 99.5%

Adjustable Flux 6 — 25 gfd (10 — 42 l/mh)

Feed TDS 0 — 10,000 mg/L

Temperature 36 to 113 deg F (2 to 45 deg C)

Maximum Pressure 450 psi (31 bar)

Inlet Pressure 10 — 60 psi (0.8 — 4.0 bar)

THE IMPRO IS AVAILABLE IN A VARIETY OF STANDARD SKID-MOUNTED CONFIGURATIONS

Model	Average Permeate Flow (gpm [m ³ /hr])	Maximum Permeate Flow (gpm [m ³ /hr])	Number of Elements
IMPRO 50	50 [11]	75 [17]	12
IMPRO 100	100 [23]	140 [32]	20
IMPRO 150	150 [34]	190 [43]	32
IMPRO 200	200 [45]	280 [64]	40
IMPRO 300	300 [68]	350 [79]	60
IMPRO 450	450 [102]	560 [127]	96
IMPRO 600	600 [136]	700 [159]	120
IMPRO 900	900 [204]	1,120 [255]	192



Americas: +1 (866) 475.0115
EMEA: +49 (0) 671 79610 325
APAC: +61 (0)2 4340 8900

[@Pall_Water](#) | [company/pallwater](#) | [info@pallwater.com](#)
[pallwater.com](#)

Pall Water has installations all over the globe. To speak to a Pall Water representative in your area, please go to [www.pallwater.com](#).

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your local representative to verify that this information remains valid.

© Copyright 2017, Pall Corporation. Pall, and Aria are trademarks of Pall Corporation. ® Indicates a trademark registered in the USA. ™ is a common law mark in the USA and is a service mark of Pall Corporation. Document ID: PWIMPROSKIDDSb.